



**HD-10C 3-Point Lift**



**HD-10DC Pull-Type**

**DOUBLE SPINDLE ROTARY CUTTERS**

MODEL #	APPROX BLADE TIP SPEED FPM	SUGGESTED HORSE POWER	DESCRIPTION	APPROX WT.
HD-10AC	13,616	55-85	10' Lift Type	2000 lbs.
HD-10DAC	13,616	55-85	10' Pull Type	2300 lbs.
HD7DC	17,329	55-85	7' Heavy-Duty Pull-Type	1955 lbs.
HD8DC	19,804	55-85	8' Heavy-Duty Pull-Type	2099 lbs.

- Heavy duty cross braced tube frame,
- 10 GA. deck w/ 8 1/2" sides-10' models
- 3/16" deck with 8 1/2" sides- 7' & 8' models
- HD-10AC & HD-10DAC have interchangeable decks
- Saucer-shaped blade carriers
- 1/4" pan w/1"X4" laminated bar, 7' & 10' models
- Oblong blade carrier 1/4" pan, 3/4"x6" bar - 8' model
- 1/2"X3 1/2" Airlift blades
- 100 H.P. gearboxes side, 150 H.P. T-Box center-10' models
- 150-H.P. gearboxes- 7' & 8' models
- Category 2 hitch & lift pins. HD-10AC
- Cast hubs w/taper bearing
- 10' Lift type is quick hitch compatible

- Laminated rubber tires 4"X8" HD-10AC, 6"X9", all pull type (Also available with Air Craft Tires on all pull type)
- Heavy duty pull tongue w/jack, all pull type
- 2" Tailwheel forkshaft HD-10AC
- Spindle type rear wheels, all pull type
- 1" to 10" Cutting height HD-10AC
- 1" to 12" Cutting height, all pull type
- 3"X8" HYD. CYL. w/stroke limiter hose and breather, all pull type
- Heavy duty shock absorbing & flexible gearbox couplings, 10' models
- Category 6 driveshaft w/torque limiter HD-10AC
- Category 6 constant velocity w/torque limiter, all pull type

**HEAVY- DUTY PULL-TYPE ROTARY CUTTER**



**HD-7DC, HD-8DC PULL TYPE**

All Howse Rotary Cutters come standard with chain guards. However, they may be purchased without chain guards if the customer prefers. Howse recommends chain guards on all Howse Rotary Cutters.